



## CHROMOLUX alu

A special label paper for non-returnable use, with a smooth metallised surface with aluminium. Available in three embossings: lin, moiré and ligné. It is also available with a primed surface suitable for UV-printing.

### FEATURES AND BENEFITS

- Superior look
- Metallised surface
- High bulk for outstanding embossing results
- Hassle-free labelling
- Direct food contact approved (ISEGA)


### APPLICATION

- Wet-glue labels for non-returnable bottles
- Food and non-food container labels
- Face stock for self-adhesive labels
- Wrap-around labels

### PRINTING

- Offset, flexo, gravure

## TECHNICAL SPECIFICATIONS

SUBSTANCE <sup>1</sup>		g/m <sup>2</sup>	80	TEST METHOD
<b>Sheets</b>			•	
<b>Caliper<sup>2</sup></b>		µm	84	DIN 53105, part 1
<b>Roughness<sup>5</sup></b>	reverse side	ml/min	< 700	DIN 53108
<b>Cobbtest<sup>3</sup></b>		g/m <sup>2</sup>	> 8	DIN 53132 (10 sec)
<b>Tensile strength<sup>3</sup></b>	dry MD	N	> 57	DIN 53112, part 1
	dry CD	N	> 27	DIN 53112, part 1
	wet MD	N	> 4.0	DIN 53112, part 1
<b>Tearing strength<sup>3</sup></b>	average	mNm/m	> 700	DIN 53115 / Brecht-Imset
	MD	mNm/m	> 680	DIN 53115 / Brecht-Imset
	CD	mNm/m	> 720	DIN 53115 / Brecht-Imset
<b>Testing Condition 50% RH at 23°C</b>				DIN 50014

<sup>1</sup> nominal <sup>2</sup> average <sup>3</sup> minimum <sup>5</sup> maximum

Subject to alteration. Status: 08/2015

joerg.neuhaeuser@zanders.com